

MIDWEST Fasteners

IHA-177 INSULATION HANGER ADHESIVE

Product Data:

MIDWEST Fasteners HANGER ADHESIVE is a high strength, heavy-bodied adhesive, specifically formulated for adhering anchors for hanging insulation.

IHA-177 HANGER ADHESIVE bonds metal and nylon anchors to metal, concrete or masonry surfaces. The product can also be used to install metal or ceramic wall fixtures and in tile applications.

MIDWEST Fasteners HANGER ADHESIVE is also available for use as a general-purpose construction adhesive in applications requiring a high strength bond, or in applications subjected to high temperatures.

Special Characteristics:

- Excellent thermal shock resistance
- High bond strength
- Water resistant
- Immediate grab
- Mildew resistant
- Non-slip formula



TYPICAL PHYSICAL PROPERTIES AND TECHNICAL INFORMATION:

Base: Thermoplastic Rubber

Type: Solvent

Solids Content: 64%

Color: Light Brown

Weight/gallon: 9.0 lbs./gal.

Shear Strength: Greater than 600 psi (AFG 01)

Water Resistance: Excellent

Consistency: Gun Grade Mastic

Application Temperature: 30°F to 120°F

Extrudability: Excellent (ASTM C 731)

Service Temperature: -30°F to 250°F

Shelf Life: 12 months

Storage Temp: Store at room temperature with cross ventilation.

Clean-up: Mineral Spirits, exercising safe practices

OSHA Class 1B liquid. Store per 29 CFR 1910, 106.

Coverage: 500-1000 anchors per gallon

Flammability: Flammable, Red Label

Flash point: (ASTM D 3828) -9°F

Open time: 15 minutes at 75°F and 50% relative humidity



450 Richard St, Miamisburg, OH 45342 | Toll Free: 800-852-8352 | Fax: 937-866-4174 | www.midwestfasteners.com

All information contained herein is subject to change without notice.