## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: Eco-Hanger Grip Adhesive Zero VOC
- · Article number: 22-15
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive.
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Mon-Eco Industries, Inc.

5 Joanna Ct.

East Brunswick, NJ 08816 Phone: 732-257-7942

· 1.4 Emergency telephone number:

ChemTel Inc.

+1 (800)255-3924, +1 (813)248-0585



#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Classifications listed are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).



> flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Additional information:

There are no other hazards not otherwise classified that have been identified.

0 % of the mixture consists of component(s) of unknown toxicity.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

(Cont'd. on page 2)

#### according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. from page 1)

#### · Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

methyl acetate

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

**Precautionary statements** 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing vapours.

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection.

P233 Keep container tightly closed.

P243 Take precautionary measures against static discharge.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403+P235 Store in a well-ventilated place. Keep cool.

· Additional information:

Restricted to professional users.

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



2 Health = 2

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Cont'd. on page 3)

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd, from page 2)

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- **Description**: Mixture of substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 79-20-9

methyl acetate

♠ Flam. Liq. 2, H225

• Eye Irrit. 2, H319; STOT SE 3, H336

25-50%

EINECS: 201-185-2

Index number: 607-021-00-X

Additional information:

For the listed ingredient(s), the identity and exact percentages are being withheld as a trade secret.

For the wording of the listed Hazard Statements refer to section 16.

#### **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

#### · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

#### · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### · After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### · After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

### · 4.2 Most important symptoms and effects, both acute and delayed

Headache

Cramp

Dizziness

Coughing

Breathing difficulty

Irritant to eyes.

Slight irritant effect on skin and mucous membranes.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Unconsciousness

#### · Hazards

Danger of impaired breathing.

(Cont'd. on page 4)

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. from page 3)

Danger of convulsion.

Danger of disturbed cardiac rhythm.

Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Medical supervision for at least 48 hours.

Monitor circulation, possible shock treatment.

If necessary oxygen respiration treatment.

#### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Gaseous extinguishing agents

Carbon dioxide

Water in flooding quantities.

Water haze or fog

- · For safety reasons unsuitable extinguishing agents: Water spray
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water fog or haze.

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Used rags or other cleaning materials should be soaked with water and placed in a sealed container.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Cont'd. on page 5)

#### according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. from page 4)

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

Rags / metal wools / cuttings / shavings and waste papers soaked with product must be placed in a sealed, metal container rated for flammable waste.

#### Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Flammable gas-air mixtures may form in empty receptacles.

#### · 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

#### · Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

#### Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see section 7.
- · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace: 79-20-9 methyl acetate		
REL (USA)	Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm	
TLV (USA)	Short-term value: 757 mg/m³, 250 ppm Long-term value: 606 mg/m³, 200 ppm	
EL (Canada)	Short-term value: 250 ppm Long-term value: 200 ppm	
•	(Cont'd on page 6)	

(Cont'd. on page 6)

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. from page 5)

EV (Canada) Short-term value: 755 mg/m³, 250 ppm Long-term value: 605 mg/m³, 200 ppm

- **DNELs** No further relevant information available.
- · PNECs No further relevant information available.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

Respiratory protection:

Suitable respiratory protective device recommended.

Use suitable respiratory protective device when high concentrations are present.

For spills, respiratory protection may be advisable.

NIOSH or EN approved organic vapour respirator equipped with a dust/mist prefilter should be used.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures See Section 7 for additional information.

### **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Paste Colour: Tan • Odour: Mild

· Odour threshold: Not determined.

· **pH-value:** Not determined.

(Cont'd. on page 7)

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

Trade name: Eco-Hanger Grip Adhesive Zero VOC

	(Cont'd. from page 6
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Not determined. 56 °C (133 °F)
· Flash point:	-13 °C (9 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto/Self-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not self-igniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
· Explosion limits: Lower: Upper:	3,1 Vol % 16,0 Vol %
· Vapour pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)
Density at 20 °C (68 °F): Relative density Vapour density at 20 °C (68 °F) Evaporation rate at 20 °C (68 °F)	1,13 g/cm³ (9,43 lbs/gal) Not determined. 2 g/cm³ (16,69 lbs/gal) (Air=1) 3.2 (N-Butyl Acetate= 1)
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity: Dynamic: Kinematic: · 9.2 Other information	Not determined. Not determined. No further relevant information available.

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: Keep away from heat and direct sunlight.
- 10.3 Possibility of hazardous reactions

Flammable.

Reacts with strong alkali.

Reacts with strong acids and oxidising agents.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

Toxic fumes may be released if heated above the decomposition point.

· 10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

(Cont'd. on page 8)

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. from page 7)

Store away from oxidising agents.

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Hydrocarbons

Danger of forming toxic pyrolysis products.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification: None.
- · Primary irritant effect:
- · Skin corrosion/irritation Slight irritant effect on skin and mucous membranes.
- Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Subacute to chronic toxicity: No further relevant information available.
- Acute effects (acute toxicity, irritation and corrosivity):

Vapours have narcotic effect.

Irritating to eyes.

- Repeated dose toxicity: Repeated exposure may cause skin dryness or cracking.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · **Aspiration hazard** Based on available data, the classification criteria are not met.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.

(Cont'd. on page 9)

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. from page 8)

· 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

### **SECTION 14: Transport information**

- · 14.1 UN-Number
- · DOT, ADR, IMDG, IATA

UN1133

· 14.2 UN proper shipping name



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

· DOT, IATA Adhesives

· ADR 1133 ADHESIVES · IMDG ADHESIVES

- · 14.3 Transport hazard class(es)
- · DOT



· Class 3 Flammable liquids.

Label

· ADR



· Class 3 (F1) Flammable liquids.

(Cont'd. on page 10)

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

Trade name: Eco-Hanger Grip Adhesive Zero VOC

	(Cont'd. from pa
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group DOT, ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler): EMS Number:	33
	F-E,S-D
14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of  Not applicable.
Transport/Additional information:	
ADR	
Transport category	2
Tunnel restriction code	D/E
IATA	Limited quantity by air: 1L
UN "Model Regulation":	UN 1133 ADHESIVES, 3, II

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- ·SARA
- Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65 (California):
- · Chemicals known to cause cancer:

None of the ingredients are listed.

(Cont'd. on page 11)

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. from page 10)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- Carcinogenic Categories
- EPA (Environmental Protection Agency)

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer)

9003-55-8 styrene-butadiene latex

3

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

- · Canada
- · Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients are listed.

· Canadian Ingredient Disclosure list (limit 1%)

79-20-9 methyl acetate

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I

None of the ingredients are listed.

- · Other regulations, limitations and prohibitive regulations
- Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

(Cont'd. on page 12)

## according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA GHS

Printing date 04.11.2015 Revision: 04.11.2015

Trade name: Eco-Hanger Grip Adhesive Zero VOC

(Cont'd. from page 11)

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

#### Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com